



PROFESSIONAL & BROADCAST DISPLAY DIGITAL SIGNAGE SOLUTIONS

www.vity.com



email: info@vity.com
phone: +33 (0)2 97 89 20 02
fax: +33 (0)2 97 89 20 10

180 rue Pierre Landais - 56850
CAUDAN - FRANCE

LCD 2011

LCV SERIES - DESKTOP VIDEO

LCV 56HX



Panel size 5.6"
Resolution 960 x 234
Display area (mm) 113 x 84
Brightness 300 cd/m²
Viewing angles H: 45/45° - V: 30/10°
Inputs 1x CVBS on RCA
1x audio on RCA
Dimensions (WxHxD) 156 x 126 x 34.5 mm
Power supply 12 VDC
Consumption 8W

LCV 70CC



Panel size 7" - wide format
Resolution 1440 x 234
Display area (mm) 154 x 87
Brightness 350 cd/m²
Contrast 150:1
Viewing angles H: 60/60° - V: 40/60°
Inputs 1x CVBS on RCA
1x audio on RCA
Dimensions (WxHxD) 180 x 115 x 30 mm
Power supply 12 VDC
Consumption 10W

LCV 80HX



Panel size 8"
Resolution 1440 x 234
Display area (mm) 154 x 87
Pitch (mm) 0.107 x 0.372
Brightness 350 cd/m²
Contrast 150:1
Viewing angles H: 55/55° - V: 15/35°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 209 x 158.5 x 31.5 mm
Power supply 12 VDC
Consumption 14W

LCV 64HX



Panel size 6.4"
Resolution 960 x 234
Display area (mm) 129 x 97
Pitch (mm) 0.171 x 0.264
Brightness 300 cd/m²
Contrast 150:1
Viewing angles H: 120° - V: 95°
Inputs 2x CVBS on RCA
Dimensions (WxHxD) 180 x 135 x 35 mm
Power supply 12 VDC
Consumption 8W

LCV 70INST



Panel size 7" - wide format
Resolution 1440 x 234
Display area (mm) 154 x 87
Brightness 350 cd/m²
Contrast 150:1
Viewing angles H: 60/60° - V: 40/60°
Inputs 1x CVBS on RCA
1x audio on RCA
Dimensions (WxHxD) 180 x 115 x 30 mm
Power supply 12 VDC
Consumption 10W

LCV 70FSDI



Panel size 7" - wide format
Resolution 1024 x 600
Display area 152.4 x 91.44 mm
Brightness 220 cd/m²
Contrast 400:1
Viewing angles H: 140° - V: 100°
Inputs 1x SDI on BNC
1x s-video on mini-din
1x CVBS on BNC
Outputs 1x SDI - 1x CVBS
Dimensions (WxHxD) 187 x 174 x 122 mm
Power supply 100/240 VAC
Consumption 20W

SDI

AXM SERIES - DESKTOP VIDEO & GRAPHIC

AXM 10WS



New!

Panel size 10.4"
Resolution 800 x 600
Display area (mm) 211.2 x 158.4
Pitch (mm) 0.264 x 0.264
Brightness 230 cd/m²
Contrast 400:1
Viewing angles H: 45/65° - V: 65/65°
Inputs 2x on RCA
1x VGA on HD15
1x audio on minijack
1x audio out minijack
Dimensions (WxHxD) 225 x 216 x 73 mm
Power supply 12 VDC
Consumption <10W

AXM 15SOBK



Panel size 15"
Resolution 1024 x 768
Display area (mm) 304.1 x 228.1
Pitch (mm) 0.297 x 0.297
Brightness 230 cd/m²
Contrast 200:1
Viewing angles H: 160° - V: 160°
Inputs 1x CVBS on RCA
1x s-video on mini-din
1x DVI on DVI-F
1x audio on mini-jack
(+1 output)
Dimensions (WxHxD) 404 x 393 x 162 mm
Power supply 12 VDC

AXM 17SOBK - 17" version

AXM 17SC



AXM 19SC - 19" version

New!

Panel size 17"
Resolution 1280 x 1024
Display area (mm) 338 x 270
Pitch (mm) 0.264 x 0.264
Brightness 250 cd/m²
Contrast 1000:1
Viewing angles H: 85/85° - V: 85/85°
Inputs 2x CVBS + 2 output
on BNC
1x s-video + 1 output
on mini-din
1x YPbPr on RCA
1x VGA + 1x DVI
2x audio + 2 output
1x audio PC
Dimensions (WxHxD) 375 x 370 x 42 mm
Power supply 12 VDC
Consumption 45W

AXM 22SW




Built-in Quad video function
Strength glass

New!

Panel size 22"
Resolution 1920 x 1080
Display colors 16.7 millions
Pitch (mm) 0.4845
Brightness 300 cd/m²
Contrast 1000:1
Viewing angles H: 170° - V: 160°
Inputs 4x CVBS on BNC
1x s-video on mini-din
1x VGA on HD15
1x YPbPr on RCA
1x HDMI on HDMI f.
1x DVI on DVI f.
1x audio in per input
1x audio out - RCA
Dimensions (WxHxD) 517 x 380 x 240 mm
Power supply 12 VDC

LCVO SERIES - OPEN FRAME VIDEO

LCVO 25PN



Panel size 2.5"
Resolution 480 x 234
Display area (mm) 49 x 37
Pitch (mm) 0.1035 x 0.160
Brightness 250 cd/m²
Contrast 350:1
Viewing angles H: 50/50° - V: 15/35°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 64 x 74 x 21 mm
Power supply 12 VDC
Consumption 3W

LCVO 40PN



Panel size 4"
Resolution 480 x 234
Display area (mm) 82 x 61
Pitch (mm) 0.171 x 0.264
Brightness 250 cd/m²
Contrast 150:1
Viewing angles H: 45/45° - V: 10/30°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 96 x 76 x 6.5 mm
Power supply 12 VDC
Consumption 3W

LCVO 56HX



Panel size 5.6"
Resolution 960 x 234
Display area (mm) 113.3 x 84.7
Pitch (mm) 0.118 x 0.362
Brightness 300 cd/m²
Contrast 150:1
Viewing angles H: 45/45° - V: 10/30°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 96 x 76 x 6.5 mm
Power supply 12 VDC
Consumption 8W

LCVO 64PN



Panel size 6.4"
Resolution 960 x 234
Display area 129 x 97 mm
Pitch (mm) 0.135 x 0.416
Brightness 330 cd/m²
Contrast 350:1
Viewing angles H: 60/60° - V: 40/55°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 174.2 x 119.7 x 20
Power supply 12 VDC
Consumption 6W

LCVO 70HX



Panel size 7" - wide format
Resolution 1440 x 424
Display area (mm) 154 x 87
Pitch (mm) 0.107 x 0.372
Brightness 400 cd/m²
Contrast 350:1
Viewing angles H: 60/60° - V: 40/50°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 166 x 100 x 20 mm
Power supply 12 VDC
Consumption 7W

LCVO 80PN



Panel size 8"
Resolution 1440 x 468
Display area 161 x 117 mm
Pitch (mm) 0.112 x 0.252
Brightness 400 cd/m²
Contrast 350:1
Viewing angles H: 55/55° - V: 15/35°
Inputs 1x CVBS on RCA
Dimensions (WxHxD) 194 x 134 x 30 mm
Power supply 12 VDC
Consumption 8.4W

AXCTO OF SERIES - OPEN FRAME VIDEO & GRAPHIC

AXCTO 70WOF



Panel size 7"
Resolution 800 x 480
Display area (mm) 152.4 x 91.44
Pitch (mm) 0.1905 x 0.1905
Brightness 350 cd/m²
Contrast 300:1
Viewing angles H: 60/60° - V: 60/40°
Inputs 1x CVBS on RCA
1x s-video on mini-din
1x VGA on HD15
Dimensions (WxHxD) 172 x 136 x 38 mm
Power supply 12 VDC
Consumption 8W

AXCTO 84OF



Panel size 8.4"
Resolution 800 x 600
Display area (mm) 170.4 x 127.8
Pitch (mm) 0.213 x 0.213
Brightness 450 cd/m²
Contrast 500:1
Viewing angles H: 60/60° - V: 40/60°
Inputs 1x CVBS on RCA
1x s-video on mini-din
1x VGA on HD15
Dimensions (WxHxD) 240 x 160 x 45 mm
Power supply 12 VDC
Consumption 15W

AXCTO 10XOF



Panel size 10.4"
Resolution 1024 x 768
Display area (mm) 210 x 158.8
Pitch (mm) 0.0685 x 0.2055
Brightness 350 cd/m²
Contrast 1200:1
Viewing angles H: 88/88° - V: 88/88°
Inputs 1x CVBS on RCA
1x s-video on mini-din
1x VGA on HD15
Dimensions (WxHxD) 260 x 215 x 38 mm
Power supply 12 VDC
Consumption 15W

AXCTO 10WXOF



Panel size 10.1" - wide format
Resolution 1024 x 600
Display area (mm) 220.4 x 129.1
Pitch (mm) 0.21525
Brightness 250 cd/m² - **LED**
Contrast 500:1
Viewing angles H: 70/70° - V: 60/50°
Inputs 1x CVBS on RCA
1x s-video on mini-din
1x VGA on HD15
Dimensions (WxHxD) 238 x 168 x 30 mm
Power supply 12 VDC
Consumption 10W

LCV xR SERIES - RACK MOUNT VIDEO

LCV 25X6R



Panel size 6x 2.5"
 Resolution 480 x 234
 Display area (mm) 49 x 37
 Pitch (mm) 0.1035 x 0.1035
 Brightness 250 cd/m²
 Contrast 350:1
 Viewing angles H: 50/50° - V: 15/35°
 Inputs 1x CVBS on BNC
 + loop + Tally
 Dimensions (WxHxD) 19" x 2U x 82 mm
 Power supply 12 VDC
 Consumption 24W

LCV 4X4RW



New!

Panel size 4x 4"
 Resolution 480 x 272 (16:9)
 Display area 87.84 x 49.78 mm
 Pitch (mm) 0.183
 Brightness 400 cd/m²
 Contrast 300:1
 Viewing angles H: 130° - V: 100°
 Inputs 2x CVBS on BNC
 + loop + Tally
 Dimensions (WxHxD) 19" x 3U x 133 mm
 Power supply 12 VDC
 Consumption 20W

LCV 4x4RHX - low cost model

Panel size 4x 4"
 Resolution 960 x 234
 Brightness 350 cd/m²
 Contrast 850:1

LCV 57X3R



Panel size 3x 5.7"
 Resolution 640 x 480
 Display area 116.2 x 87.2 mm
 Pitch (mm) 0.1815 x 0.1815
 Brightness 220 cd/m²
 Contrast 300:1
 Viewing angles H: 140° - V: 100°
 Inputs 1x CVBS on BNC
 Tally on DB9
 Outputs 1x CVBS on BNC
 Dimensions (WxHxD) 19" x 3U
 Power supply 12 VDC
 Consumption 36W

SDI

LCV 57x3RFSDI
 Same specifications as **LCV 57x3R** above
 with SDI inputs on BNC.

SDI



LCV 57x3R
rear panel



LCV 57x3R
front panel

AXRTO SERIES - RACK MOUNT VIDEO & GRAPHIC

AXRTO 70X2R



Panel size 2x 7"
 Resolution 800 x 480
 Display area (mm) 152.4 x 91.5
 Brightness 600 cd/m²
 Contrast 500:1
 Viewing angles H: 70/70° - V: 60/50°
 Inputs 1x CVBS on BNC
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 3U x 95.5 mm
 Power supply 12 VDC
 Consumption 20W

SDI

LCV 70x2RFSDI
 Same specifications as **AXRTO 70x2R** above
 with SDI inputs on BNC and without VGA.

AXRTO 84X2R



Panel size 2x 8.4"
 Resolution 800 x 600
 Display area (mm) 170 x 128
 Brightness 350 cd/m²
 Contrast 500:1
 Viewing angles H: 60/60° - V: 60/40°
 Inputs 2x CVBS on BNC + 1 output
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 4U x 71 mm
 Power supply 12 VDC
 Consumption 20W

SDI

LCV 84x2RFSDI
 Same specifications as **AXRTO 70x2R** above
 with SDI inputs on BNC and without VGA.

AXRTO 15R



Panel size 15"
 Resolution 1024 x 768
 Display area 304 x 228 mm
 Pitch (mm) 0.297
 Brightness 350 cd/m²
 Contrast 300:1
 Viewing angles H: 60/60° - V: 50/50°
 Inputs 2x CVBS on BNC + 1 output
 1x s-video on mini-din
 1x VGA on HD15
 Dimensions (WxHxD) 19" x 7U x 51 mm
 Power supply 12 VDC
 Consumption 30W

AXRTO 10R - 10" version
AXRTO 12R - 10" version
AXRTO 17R - 17" version
AXRTO 19R - 19" version

AXRTO 15WFSDI



Panel size 15" - wide format
 Resolution 1280 x 800
 Display area 331 x 207 mm
 Brightness 300 cd/m²
 Contrast 400:1
 Viewing angles H: 90° - V: 50°
 Inputs 1x SDI on BNC + 1out
 2x CVBS on BNC + 1 out
 1x s-video on mini-din
 1x VGA on HD15
 1x Tally on SUBD9
 SDI inputs SD-SDI 270 Mbps
 521i - 625i
 Dimensions (WxHxD) 19" x 7U x 87.5 mm
 Power supply 12VDC
 Consumption 28W

SDI

AXRTO 15FSDI - 4:3 version

