

VSWMT 121



Multi-selector 12 inputs

SPECIFICATIONS

Presentation selector 12 inputs
3 selectors by 1: 1 composite video selector 4x1, 1 VGA selector 4x1, 1 DVI selector 4x1
Stereo audio associated to each selector
Micro input with adjustable volume
Control by RS-232, IR and front buttons
Format rack 1U
RS232/485 output to control the commutation of the visual display unit



Applications: video signal selections for meeting rooms, conference rooms, amphitheatres, stores, ...

TECHNICAL DATAS

MAIN SPECIFICATIONS

Inputs	4x composite video on BNC f. 4x DVI on DVI-D f. port 4x VGA on HD-15 f. 12x stereo audio (4 jack 3.5mm pour VGA, 4xintervals for the composite video and 4xintervals for the DVI 1x micro inputs on jack
Outputs	1x composite video on BNC f. 1x DVI on DVI-D f. port 1x VGA on HD-15 f. 3x stereo audio (1 jack 3.5mm for VGA, 1xintervals for the composite video and 1xintervals for the DVI 1x RS232/485 on intervals)
Output resolutions	1920x1200 max for the DVI selector 3200x2400 max for the VGA selector
Control	RS-232 and infrared

POWER SUPPLY AND CONSUMPTION

Power Supply	230 VAC
Consumption	25 W

WEIGHT AND SIZES

Sizes (W x H x D)	482 x 242 x 44 mm
Weight	2 Kg

VITY TECHNOLOGY
180 rue Pierre Landais
56 850 Caudan - France

Tel.: +33 (0)2 97 89 20 02
Fax.: +33 (0)2 97 89 20 10

info@vity.com
www.vity.com